


Digital Isolator CMOS 4-CH 150Mbps 16-Pin SOIC N Tube

Manufacturers	Analog Devices, Inc
Package/Case	SOIC
Product Type	Interface ICs
RoHS	Pb-free Halide free
Lifecycle	



Images are for reference only

Please submit RFQ for ADUM141D0BRZ or [Email to us: sales@ovaga.com](mailto:sales@ovaga.com) We will contact you in 12 hours.

[RFQ](#)

General Description

The ADuM141D is a quad-channel digital isolator based on Analog Devices, Inc., iCoupler® technology. Combining high speed, complementary metal-oxide semiconductor (CMOS) and monolithic air core transformer technology, these isolation components provide outstanding performance characteristics superior to alternatives such as optocoupler devices and other integrated couplers. The maximum propagation delay is 13 ns with a pulse width distortion of less than 3 ns at 5 V operation. Channel matching is tight at 3.0 ns maximum.

The ADuM141D data channels are independent and are available in a variety of configurations with a withstand voltage rating of 3.0 kV rms or 3.75 kV rms. The devices operate with the supply voltage on either side ranging from 1.8 V to 5 V, providing compatibility with lower voltage systems as well as enabling voltage translation functionality across the isolation barrier.

Unlike other optocoupler alternatives, dc correctness is ensured in the absence of input logic transitions. Two different fail-safe options are available, by which the outputs transition to a predetermined state when the input power supply is not applied or the inputs are disabled. The ADuM140E1/ADuM141E1/ADuM142E1 is pin-compatible with the ADuM1400/ADuM1401/ADuM1402.

Features

High common-mode transient immunity: 100 kV/ μ s

High robustness to radiated and conducted noise

Low propagation delay

13 ns maximum for 5 V operation

15 ns maximum for 1.8 V operation

150 Mbps maximum guaranteed data rate

Safety and regulatory approvals

UL recognition

3000 V rms/3750 V rms for 1 minute per UL 1577

CSA Component Acceptance Notice 5A

VDE certificate of conformity

DIN V VDE V 0884-10 (VDE V>

CQC certification per GB4943.1-2011

Backward compatibility

ADuM140E1/ADuM141E1/ADuM142E1 pin-compatible with
ADuM1400/ADuM1401/ADuM1402

Low dynamic power consumption

1.8 V to 5 V level translation

High temperature operation: 125°C

Fail-safe high or low options

16-lead, RoHS compliant, SOIC package

Qualified for automotive applications


Application

General-purpose multichannel isolation

Serial peripheral interface (SPI)/data converter
isolation

Industrial field bus isolation

Related Products



[ADV7181CBSTZ](#)

Analog Devices, Inc
LQFP-64



[AD8170AR](#)

Analog Devices, Inc
SOP8



[AD724JR](#)

Analog Devices, Inc
SOIC-16



[ADV7393BCPZ](#)

Analog Devices, Inc
LFCSP-VQ-40



[ADV7391WBCPZ](#)

Analog Devices, Inc
LFSCP-3




[ADV7390BCPZ](#)

Analog Devices, Inc
QFN32



[ADV7341BSTZ](#)

Analog Devices, Inc
LQFP-64



[ADUM4160BRIZ](#)

Analog Devices, Inc
SOIC-16