

LTC490IS8#PBF

Data Sheet

Transceiver RS422/RS485, 4.75V-5.25V supply, SOIC-8

Manufacturers <u>Analog Devices, Inc</u>

Package/Case SOP8

Product Type Interface ICs

RoHS Pb-free Halide free



Images are for reference only

Please submit RFQ for LTC490IS8#PBF or Email to us; sales@ovaga.com We will contact you in 12 hours.

RFO

General Description

Lifecycle

The LTC490 is a low power differential bus/line transceiver designed for multipoint data transmission standard RS485 applications with extended common mode range (12V to -7V). It also meets the requirements of RS422.

The CMOS design offers significant power savings over its bipolar counterpart without sacrificing ruggedness against overload or ESD damage.

Excessive power dissipation caused by bus contention or faults is prevented by a thermal shutdown circuit which forces the driver outputs into a high impedance state. The receiver has a fail safe feature which guarantees a high output state when the inputs are left open.

Both AC and DC specifications are guaranteed from 0°C to 70°C and 4.75V to 5.25V supply voltage range.

Features

Low Power:>

Designed for RS485 or RS422 Applications

Single 5V Supply

Thermal Shutdown Protection

Power-Up/Down Glitch-Free Driver Outputs Permit Live Insertion or Removal of Package

Driver Maintains High Impedance with the Power Off

Combined Impedance of a Driver Output and Receiver Allows up to 32 Transceivers on the Bus

70mV Typical Input Hysteresis

28ns Typical Driver Propagation Delays with 5ns Skew for 2.5MB Operation

Pin Compatible with the SN75179

Available in 8-Lead PDIP and SO Packages

Related Products



LTC4300A-1IMS8#PBF

Analog Devices, Inc MSOP8



LTC2870IFE#PBF

Analog Devices, Inc TSSOP28



LTC6820HMS#PBF

Analog Devices, Inc MSOP-16



LTC2854HDD#PBF

Analog Devices, Inc QFN-10



Low Power RS485/RS422 Transceiver

Level Translator





LTC6820IMS#PBF

Analog Devices, Inc MSOP16



LTM2881IV-3#PBF

Analog Devices, Inc LGA32



LTC2852IDD#PBF

Analog Devices, Inc DFN10