

24LC128-I/P

Data Sheet

EEPROM, 128 Kbit, 16K x 8bit, Serial I2C (2-Wire), 400 kHz, DIP, 8 Pins

Manufacturers	Microchip Technology, Inc	
Package/Case	PDIP-8	
Product Type	Memory	7111
RoHS	Rohs	
Lifecycle		Images are for reference only

Please submit RFQ for 24LC128-I/P or Email to us: sales@oyaga.com We will contact you in 12 hours.

<u>RFO</u>

General Description

The Microchip Technology Inc. 24AA128/24LC128/24FC128 (24XX128*) is a 16K x 8 (128 Kbit) SerialElectrically Erasable PROM (EEPROM), capable of operation across a broad voltage range (1.7V to 5.5V). It has been developed for advanced, low-powerapplications such as personal communications or dataacquisition. This device also has a page write capability of up to 64 bytes of data. This device is capable of both random and sequential reads up to the 128K boundary. Functional address lines allow up to eightdevices on the same bus, for up to 1 Mbit addressspace. This device is available in the standard 8-pinplastic DIP, SOIC (3.90 mm and 5.28 mm), TSSOP, MSOP, DFN, and Chip Scale packages.

Related Products



AT24CM02-SSHM-B

Microchip Technology, Inc SOIC-8

24FC512-I/SM Microchip Technology, Inc SOIJ-8





AT24CM02-SSHD-B

Microchip Technology, Inc SOIC-8

24AA512-I/SM

Microchip Technology, Inc SOIJ-8



AT24C512C-SSHM-T

Microchip Technology, Inc SOIC-8



24LC256-I/ST

Microchip Technology, Inc TSSOP-8



24LC32AT-I/SN

Microchip Technology, Inc SOIC-8



AT24C04D-MAHM-T

Microchip Technology, Inc UDFN-8