

ATSAMD11C14A-SSUT

Data Sheet

RFO

ARM MCU, SAM D Series, SAM32 Family SAM D1X Series Microcontrollers, ARM Cortex-M0+, 32bit, 48 MHz

Manufacturers	Microchip Technology, Inc	a series
Package/Case	SOIC-14	The Se
Product Type	Embedded Processors & Controllers	13
RoHS		
Lifecycle		Images are for reference only

Please submit RFQ for ATSAMD11C14A-SSUT or Email to us: sales@ovaga.com We will contact you in 12 hours.

General Description

A low-power, high-performance ARM® Cortex®-M0+ based flash microcontroller, the Microchip's ATSAMD11C14 is ideal for a wide range of home automation, consumer, metering and industrial applications. It features:

16KB of flash memory and 4KB of SRAM

Up to 48MHz operating frequency

Two serial communication modules (SERCOM) configurable as UART/USART, SPI or I2C, two 16-bit timer/counters, 32-bit Real-Time Clock and calendar, 12 PWM channels, one 5-channel 12-bit ADC, one 10-bit DAC

Full-Speed USB device

Supports 7/12 self-capacitance touch channels in low/high pincount devices

Supports 72 mutual-capacitance touch channels

1.62V to 3.63V power supply

Easy pin migration to SAMD11D devices

Supported by Atmel Studio, ASF and the SAM D11 Xplained Pro kit

Supported by MPLAB X IDE and MPLAB Harmony.

Features

Processor

ARM Cortex-M0+ CPU running at up to 48MHz

Single-cycle hardware multiplier

Micro Trace Buffer

Memories

16KB in-system self-programmable Flash

4KB SRAM Memory

System

Power-on reset (POR) and brown-out detection (BOD)

Internal and external clock options with 48MHDigital Frequency Locked Loop (DFLL48M) and 48MHto 96MHFractional

Digital Phase Locked Loop (FDPLL96M)

External Interrupt Controller (EIC)

8 external interrupts

One non-maskable interrupt

Two-pin Serial Wire Debug (SWD) programming, test and debugging interface

Low Power

Idle and standby sleep modes

SleepWalking peripherals

Peripherals

6-channel Direct Memory Access Controller (DMAC)

6-channel Event System

Two 16-bit Timer/Counters (TC), configurable as either:

One 16-bit TC with compare/capture channels

One 8-bit TC with compare/capture channels

One 32-bit TC with compare/capture channels, by using two TCs

One 24-bit Timer/Counters for Control (TCC), with extended functions:

Up to four compare channels with optional complementary output

Generation of synchronized pulse width modulation (PWM) pattern across port pins

Ovaga Technologies Limited

Deterministic fault protection, fast decay and configurable dead-time between complementary output Dithering that increase resolution with up to 5 bit and reduce quantization error 32-bit Real Time Counter (RTC) with clock/calendar function Watchdog Timer (WDT) CRC-32 generator One full-speed (12Mbps) Universal Serial Bus (USB) 2.0 interface Embedded device function Eight endpoints Can run from internal RC oscillator Two Serial Communication Interfaces (SERCOM), each configurable to operate as either: USART with full-duplex and single-wire half-duplex configuration I2C Bus up to 3.4MHz SMBUS/PMBUS SPI LIN slave 12-bit, 350ksps Analog-to-Digital Converter (ADC) with up to 5 channels Differential and single-ended input 1/2x to 16x programmable gain stage Automatic offset and gain error compensation Oversampling and decimation in hardware to support 13-, 14-, 15- or 16-bit resolution 10-bit, 350ksps Digital-to-Analog Converter (DAC) Two Analog Comparators (AC) with window compare function Peripheral Touch Controller (PTC) Up to 72-channel capacitive touch and proximity sensing I/O 12 GPIO pins Packages 14-pin SOIC

Ovaga Technologies Limited

Operating Voltage

1.62V - 3.63V

Related Products



ATSAMA5D36A-CU

Microchip Technology, Inc LFBGA-324

ATXMEGA128D3-AU

Microchip Technology, Inc TQFP-64



ovage

ATMEGA64M1-15AZ

Microchip Technology, Inc TQFP-32

ATTINY48-MU

Microchip Technology, Inc VQFN-32









ATMEGA32M1-AU

Microchip Technology, Inc TQFP-32

ATTINY2313V-10SU

Microchip Technology, Inc SOIC-20

ATMEGA16L-8PU

Microchip Technology, Inc PDIP-40

ATTINY4-TSHR

Microchip Technology, Inc SOT-23-6