


DC DC CONVERTER 0.6-5.5V 2.5A

Manufacturers	Analog Devices, Inc
Package/Case	LGA-25
Product Type	Power Management ICs
RoHS	
Lifecycle	



Images are for reference only

Please submit RFQ for LTM4622IV#PBF or [Email to us: sales@ovaga.com](mailto:sales@ovaga.com) We will contact you in 12 hours.

[RFQ](#)

General Description

The LTM4622 is a complete dual 2.5A step-down switching mode μ Module[®] (micromodule) regulator in a tiny ultrathin 6.25mm × 6.25mm × 1.82mm LGA and 6.25mm × 6.25mm × 2.42mm BGA packages. Included in the package are the switching controller, power FETs, inductor and support components. Operating over an input voltage range of 3.6V to 20V, the LTM4622 supports an output voltage range of 0.6V to 5.5V, set by a single external resistor. Its high efficiency design delivers dual 2.5A continuous, 3A peak, output current. Only a few ceramic input and output capacitors are needed.

The LTM4622 supports selectable Burst Mode operation and output voltage tracking for supply rail sequencing. Its high switching frequency and current mode control enable a very fast transient response to line and load changes without sacrificing stability.

Fault protection features include input overvoltage, output overcurrent and overtemperature protection.

The LTM4622 is available with SnPb (BGA) or RoHS compliant terminal finish.

Vin Range Vout Range IOU TLTM4622 3.6V to 20V 0.6V to 5.5V Dual 2.5A or Single 5A LTM4622A 3.6V to 20V 1.5V to 12V Dual 2A or Single 4A

Features

Complete Solution in <1cm²

Wide Input Voltage Range: 3.6V to 20V

3.3V Input Compatible with VIN Tied to INTVCC

0.6V to 5.5V Output Voltage

Dual 2.5A (3A Peak) or Single 5A Output Current

Current Mode Control, Fast Transient Response

External Frequency Synchronization

Multiphase Parallelable with Current Sharing

Output Voltage Tracking and Soft-Start Capability

Selectable Burst Mode® Operation

Overvoltage Input and Overtemperature Protection

Power Good Indicators

6.25mm × 6.25mm × 1.82mm LGA and 6.25mm × 6.25mm × 2.42mm BGA Packages

Application

General Purpose Point of Load Conversion

Telecom, Networking and Industrial Equipment

Medical Diagnostic Equipment

Test and Debug Systems

Related Products



[LT3763EFE](#)

Analog Devices, Inc
TSSOP28



[LT1038CK](#)

Analog Devices, Inc
TO-3



[LTC4417IUF](#)

Analog Devices, Inc
QFN-24



[LTC3440EMS](#)

Analog Devices, Inc
MSOP10



[LTC1966CMS8#PBF](#)

Analog Devices, Inc
MSOP-8P




[LTC2990IMS#PBF](#)

Analog Devices, Inc
10MSOP



[LTM8045EY#PBF](#)

Analog Devices, Inc
BGA40



[LT4295IUFD#PBF](#)

Analog Devices, Inc
28-WFQFN