

16 BIT MCU/DSP 44LD 30MIPS 48KB FLASH PB FREE, -40C to +85C, 44-TQFP, TRAY, Microcontrollers (MCU) General Purpose

Manufacturers	Microchip Technology, Inc
Package/Case	TQFP-44
Product Type	Embedded Processors & Controllers
RoHS	
Lifecycle	



Images are for reference only

Please submit RFQ for DSPIC30F4013-30I/PT or [Email to us: sales@ovaga.com](mailto:sales@ovaga.com) We will contact you in 12 hours.

[RFQ](#)

General Description

dsPIC30F Motor Control 16-bit Digital Signal Controller. Seamless migration options from this device to dsPIC33F and PIC24 devices in similar packages.

For product comparison, please consider: dsPIC33EV64GM104

Features

High-Performance dsPIC30F core

Modified Harvard architecture

C compiler optimized instruction set architecture

24-bit wide instructions, 16-bit wide data path

Up to 30 MIPS operation

DSP Engine for math intensive operations

Modulo and Bit-Reversed Addressing modes

Two, 40-bit wide accumulators with optional saturation logic

17-bit x 17-bit single cycle hardware fractional/ integer multiplier

Single cycle Multiply-Accumulate (MAC) operation

40-stage Barrel Shifter

Dual data fetch

Operating Conditions

Wide operating voltage range (2.5V to 5.5V)

Industrial and Extended temperature ranges

Peripheral Features

High current sink/source I/O pins: 25 mA/25 mA

Optionally pair up 16-bit timers into 32-bit timer modules

3-wire SPI™ modules (supports 4 Frame modes)

I2C™ module supports Multi-Master/Slave mode and 7-bit/10-bit addressing

Addressable UART modules with FIFO buffers and selectable pins

Data Converter Interface (DCI) supports common audio Codec protocols, including I2S and AC'97

CAN bus module compliant with CAN 2.0B standard

Analog Features

12-bit 200 Ksps Analog-to-Digital Converter (A/D)

A/D Conversion available during Sleep and Idle

1 Sample/Hold

Multiple Conversion Sequencing Options

Special Microcontroller Features

Enhanced Flash program memory with 10,000 erase/write cycle (min.) for industrial temperature range, 100K (typical)

Data EEPROM memory with 100,000 erase/write cycle (min.) for industrial temperature range, 1M (typical)

Self-reprogrammable under software control

Power-on Reset (POR), Power-up Timer (PWRT) and Oscillator Start-up Timer (OST)

Flexible Watchdog Timer (WDT) with on-chip low power RC oscillator for reliable operation

Fail-Safe clock monitor operation

Detects clock failure and switches to on-chip low power RC oscillator

Programmable code protection

In-Circuit Serial Programming™ (ICSP™)

DC to 40 MHz external clock input

Internal FRC input with PLL active (4x, 8x, 16x)

4 MHz-10 MHz oscillator input with PLL active (4x, 8x, 16x)

10 MHz - 20 MHz oscillator input in HS/2 or HS/3 with PLL active (4x, 8x, 16x)

Programmable Brown-out Detection and Reset generation


Sleep, Idle and Alternate Clock modes for power management

Related Products



[DSPIC30F6014A-20E/PF](#)

Microchip Technology, Inc
TQFP-80



[DSPIC30F5011-30I/PT](#)

Microchip Technology, Inc
TQFP-64



[DSPIC33EJ256MC710-I/PF](#)

Microchip Technology, Inc
TQFP-100



[DSPIC30F5015-30I/PT](#)

Microchip Technology, Inc
TQFP-64



[DSPIC33EP512MU814-I/PH](#)

Microchip Technology, Inc
TQFP-144



[DSPIC33EP512GM710-I/PF](#)

Microchip Technology, Inc
TQFP-100



[DSPIC33EJ256GP710-I/PF](#)

Microchip Technology, Inc
TQFP-100



[DSPIC30F4011-30I/PT](#)

Microchip Technology, Inc
TQFP-44