

16 BIT MCU/DSP 44LD 40MIPS 64KB FLASH, -40C to +85C, 44-TQFP, TRAY, Digital signal processorer och kontroller (DSP, DSC) 16B DSC 64KB DMA 40MIPS

Manufacturers	Microchip Technology, Inc
Package/Case	TQFP-44
Product Type	Embedded Processors & Controllers
RoHS	Rohs
Lifecycle	



Images are for reference only

Please submit RFQ for DSPIC33FJ64GP804-I/PT or [Email to us: sales@ovaga.com](mailto:sales@ovaga.com) We will contact you in 12 hours.

[RFQ](#)

General Description

- dsPIC33Fs are designed to execute digital filter algorithms and high-speed precision digital control loops, ideal for applications that need to perform under pressure
- General Purpose Digital Signal Controllers (DSCs) with advanced analog and seamless migration options to PIC24F, PIC24H MCUs and dsPIC30F DSCs

Features

Operating Range

Up to 40 MIPS operation (at 3.0-3.6V)

3.0V to 3.6V, -40°C to +150°C, DC to 20 MIPS

3.0V to 3.6V, -40°C to +125°C, DC to 40 MIPS

High-Performance dsPIC33FJ core

Modified Harvard architecture

C compiler optimized instruction set

24-bit wide instructions, 16-bit wide data path

Linear program memory addressing up to 4M instruction words

Linear data memory addressing up to 64 Kbytes

Two 40-bit accumulators with rounding and saturation options

Indirect, Modulo and Bit-reversed addressing modes

16 x 16 fractional/integer multiply operations

32/16 and 16/16 divide operations

Single-cycle multiply and accumulate (MAC) with accumulator write back and dual data fetch

Single-cycle MUL plus hardware divide

Up to ± 16 -bit shifts for up to 40-bit data

On-chip Flash and SRAM

Direct Memory Access (DMA)

8-channel hardware DMA

Up to 2 Kbytes dual ported DMA buffer area (DMA RAM) to store data transferred via DMA

Most peripherals support DMA

Timers/Capture/Compare/PWM

Up to five 16-bit and up to two 32-bit Timers/Counters

One timer runs as a Real-Time Clock with an external 32.768 kHz oscillator

Input Capture (up to four channels) with Capture on up, down or both edges

16-bit capture input functions

4-deep FIFO on each capture

Output Compare (up to four channels) with Single or Dual 16-bit Compare mode and 16-bit Glitchless PWM mode

Hardware Real-Time Clock/Calendar (RTCC)

Interrupt Controller

5-cycle latency

118 interrupt vectors

Up to 49 available interrupt sources

Up to three external interrupts

Seven programmable priority levels

Five processor exceptions

Digital I/O

Peripheral pin Select functionality

Up to 35 programmable digital I/O pins

Wake-up/Interrupt-on-Change for up to 21 pins

Output pins can drive from 3.0V to 3.6V

Up to 5V output with open drain configuration

All digital input pins are 5V tolerant

4 mA sink on all I/O pins

System Management

Flexible clock options: External, crystal, resonator and internal RC

Fully integrated Phase-Locked Loop (PLL)

Extremely low jitter PLL

Power-up Timer

Oscillator Start-up Timer/Stabilizer

Watchdog Timer with its own RC oscillator

Fail-Safe Clock Monitor

Reset by multiple sources

Power Management

On-chip 2.5V voltage regulator

Switch between clock sources in real time

Idle, Sleep, and Doze modes with fast wake-up

Analog-to-Digital Converters (ADCs)

10-bit, 11 Msps or 12-bit, 500 Ksps conversion:

Two and four simultaneous samples (10-bit ADC)

Up to 13 input channels with auto-scanning

Conversion start can be manual or synchronized with one of four trigger sources

Conversion possible in Sleep mode

Other Analog Peripherals

Two analog comparators with programmable input/output configuration

4-bit DAC with two ranges for analog comparators

16-bit dual channel 100 Ksps audio DAC

Data Converter Interface (DCI) module

Codec interface

Supports I2S and AC.97 protocols

Up to 16-bit data words, up to 16 words per frame

4-word deep TX and RX buffers

Communication Modules

4-wire SPI (up to two modules) with I/O interface to simple codecs

I2C™ with Full Multi-Master Slave mode support, slave address masking, 7-bit and 10-bit addressing, integrated signal conditioning and bus collision detection

UART (up to two modules) with LIN bus support, IrDA® and hardware flow control with CTS and RTS

Enhanced CAN (ECAN) module (1 Mbaud) with 2.0B support

Parallel Master Slave Port (PMP/EPSP)

Programmable Cyclic Redundancy Check (CRC)

Debugger Development Support

In-circuit and in-application programming

Two program breakpoints

Trace and run-time watch

Related Products



[DSPIC30F6014A-20E/PE](#)

Microchip Technology, Inc
TQFP-80



[DSPIC33EP512MU814-I/PH](#)

Microchip Technology, Inc
TQFP-144



[DSPIC30F5011-30I/PT](#)

Microchip Technology, Inc
TQFP-64



[DSPIC33EP512GM710-I/PE](#)

Microchip Technology, Inc
TQFP-100



[DSPIC33FJ256MC710-I/PE](#)

Microchip Technology, Inc
TQFP-100



[DSPIC33FJ256GP710-I/PE](#)

Microchip Technology, Inc
TQFP-100



[DSPIC30F5015-30I/PT](#)

Microchip Technology, Inc
TQFP-64



[DSPIC30F4011-30I/PT](#)

Microchip Technology, Inc
TQFP-44