

16 Bit MCU/DSP 44LD 48KB FLASH, -40C to +85C, 44-TQFP, TRAY, Microcontrollers
(MCU) 16 Bit MCU/DSP 20M 48KB FL

Manufacturers	Microchip Technology, Inc
Package/Case	TQFP-44
Product Type	Embedded Processors & Controllers
RoHS	Rohs
Lifecycle	



Images are for reference only

Please submit RFQ for DSPIC30F4011-20I/PT or [Email to us: sales@ovaga.com](mailto:sales@ovaga.com) We will contact you in 12 hours.

[RFQ](#)

General Description

dsPIC30F Motor Control 16-bit Digital Signal Controller. Seamless migration options from this device to dsPIC33F and PIC24 devices in similar packages.

For product comparison, please consider: dsPIC33EV64GM104

Features

High-Performance dsPIC30F core

Modified Harvard architecture

C compiler optimized instruction set architecture

24-bit wide instructions, 16-bit wide data path

Up to 30 MIPS operation

DSP Engine for math intensive operations

Modulo and Bit-Reversed Addressing modes

Two, 40-bit wide accumulators with optional saturation logic

17-bit x 17-bit single cycle hardware fractional/ integer multiplier

Single cycle Multiply-Accumulate (MAC) operation

40-stage Barrel Shifter

Dual data fetch

Operating Conditions

Wide operating voltage range (2.5V to 5.5V)

Industrial and Extended temperature ranges

Peripheral Features

High current sink/source I/O pins: 25 mA/25 mA

Optionally pair up 16-bit timers into 32-bit timer modules

3-wire SPI™ modules (supports 4 Frame modes)

I2C™ module supports Multi-Master/Slave mode and 7-bit/10-bit addressing

Addressable UART modules with FIFO buffers

1 CAN module, 2.0B compliant

Motor Control PWM Module Features

Motor Control PWM Module with Complementary or Independent Output modes

Edge and Center Aligned modes

Multiple duty cycle generators

Dedicated time base with 4 modes

Programmable output polarity

Dead time control for Complementary mode

Manual output control

Trigger for synchronized A/D conversions

Quadrature Encoder Interface Module Features

QEI with Phase A, Phase B and Index Pulse input

16-bit up/down position counter

Count direction status

Position Measurement (x2 and x4) mode

Programmable digital noise filters on inputs

Alternate 16-bit Timer/Counter mode

Interrupt on position counter rollover/underflow

Analog Features

10-bit 1 Msps Analog-to-Digital Converter (A/D)

A/D Conversion available during Sleep and Idle

4 Sample/Hold Channels

Multiple Conversion Sequencing Options

Special Microcontroller Features

Enhanced Flash program memory with 10,000 erase/write cycle (min.) for industrial temperature range, 100K (typical)

Data EEPROM memory with 100,000 erase/write cycle (min.) for industrial temperature range, 1M (typical)

Self-reprogrammable under software control

Power-on Reset (POR), Power-up Timer (PWRT) and Oscillator Start-up Timer (OST)

Flexible Watchdog Timer (WDT) with on-chip low power RC oscillator for reliable operation

Fail-Safe clock monitor operation

Detects clock failure and switches to on-chip low power RC oscillator

Programmable code protection

In-Circuit Serial Programming™ (ICSP™)

DC to 40 MHz external clock input

4 MHz-10 MHz oscillator input with PLL active (4x, 8x, 16x)

Programmable Brown-out Detection and Reset generation

Sleep, Idle and Alternate Clock modes for power management

Related Products



[DSPIC30F6014A-20E/PE](#)

Microchip Technology, Inc
TQFP-80



[DSPIC33EP512MU814-I/PH](#)

Microchip Technology, Inc
TQFP-144



[DSPIC30F5011-30I/PT](#)

Microchip Technology, Inc
TQFP-64



[DSPIC33EP512GM710-I/PE](#)

Microchip Technology, Inc
TQFP-100



[DSPIC33FJ256MC710-I/PE](#)

Microchip Technology, Inc
TQFP-100



[DSPIC33FJ256GP710-I/PE](#)

Microchip Technology, Inc
TQFP-100



[DSPIC30F5015-30I/PT](#)

Microchip Technology, Inc
TQFP-64



[DSPIC30F4011-30I/PT](#)

Microchip Technology, Inc
TQFP-44