

# FSA4157L6X

Data Sheet

 Image & Reel,Multiplexer Subtry HCs SPDT analog Switch 1 Ohm LV

 Manufacturers
 ON Semiconductor, LLC

 Package/Case
 MicroPak-6 Wide

 Product Type
 Interface ICs

 RoHS
 Green

 Lifecycle
 Images are for reference only

# **General Description**

FSA4157 and FSA4157A are high performance Single Pole/Double Throw (SPDT) analog switches. Both devices feature ultra low RON of 1.15Ω maximum at 4.5V VCC and operates over a wide VCC range of 1.65V to 5.5V for FSA4157, and 2.7V to 5.5V for FSA4157A. The device is fabricated with sub-micron CMOS technology to achieve fast switching speeds and is designed for break-before-make operation. The select input is TTL level compatible. The FSA4157A features very low quiescent current even when the control voltage is lower than the VCC supply. This feature services the mobile handset applications very well allowing for the direct interface with baseband processor general purpose I/Os.

# Application

ONSEMI

#### **Related Products**

<u>FSA4159P6X</u>

ON Semiconductor, LLC SC-70

**FSA4157AP6X** 



ON Semiconductor, LLC SC-70-6



ON Semiconductor, LLC SC-70-6

## FSA4157P6

**FSA5157P6X** 



ON Semiconductor, LLC SC-70-6

#### FSA1156P6X

ON Semiconductor, LLC SC-70-6

### FSUSB74MPX



ON Semiconductor, LLC MLP-16



FSA660TMX ON Semiconductor, LLC 18-XFQFN



## FSA553UCX

ON Semiconductor, LLC 9-UFBGA, WLCSP